

Eaton's Wiring Devices
USB charging devices



Combination USB Devices

Conveniently charges electronic
devices without an adapter

EATON

Powering Business Worldwide



Innovative solutions for fast and convenient charging!

Charging solutions for every device

Eaton's USB chargers offer fast, convenient and efficient charging of portable electronic devices directly from a standard outlet without bulky adapters or powered computers. This innovative line eliminates clutter in residential and commercial environments while enabling compatibility with USB Type A and C electronics, including smart phones, tablets, e-readers, cameras, MP3 players and more.

Perfect for use in residential, commercial and healthcare applications

- Homes
- Offices
- Hotels
- Lounges and coffee houses
- OEM applications
- Airports



TR
TAMPER
RESISTANT

USB-C charging devices

USB-C duplex receptacle offers fast, convenient and efficient charging of Type C devices

- Dual 3A Type-C charging capacity
- Reversible ports allow for consistent charging regardless of plug-in orientation
- Compatible with Type-C electronic devices
- Available in 15A & 20A



TR
TAMPER
RESISTANT

USB charging devices

Quick and easy access for both USB charging and electrical outlets


- 3.1A charging capacity on USB duplex receptacles
- Available in single and duplex configurations
- 15A & 20A for multiple locations
- Available in 15A & 20A and hospital grade



USB charging station

Four USB charging ports rated at 5.0A total for quick and convenient charging

- Charge up to 4 devices at the same time
- Replaces a standard receptacle



USB-C charging devices



TRUSBC15



TRUSBC20

Product description

2-pole, 3-wire grounding
 15A, 125V/AC, 5V/DC, 5.0A
 20A, 125V/AC, 5V/DC, 5.0A
 NEMA 5-15R, 5-20R

Design features

- Standard AC receptacle with two USB-C ports rated at a combined 5.0A
- Dual USB-C charging ports charge most electronic devices that comply with the USB-C standard
- Tamper resistant shutters provide compliance with 2017 NEC® Article 406.12 that states that all 15A and 20A, 125V receptacles installed in dwelling units must be tamper resistant
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure, provides redundant measure of ground continuity where jumper is used
- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Steel mounting strap is zinc plated for added corrosion resistance
- Convenient patented built-in wire strippers speed installation
- Triple wipe blade contacts and double wipe ground contacts to insure long-term blade retention
- Replaces a standard duplex receptacle



USB-C charger with TR duplex receptacle



Rating		USB Rating		Description	Color suffix	Catalog no.
A	V/AC	A	V/DC			
15	125	5.0	5	5.0A USB-C charger with TR duplex receptacle	BK, GY, LA, V, W	<input type="checkbox"/> TRUSBC15__
20	125	5.0	5	5.0A USB-C charger with TR duplex receptacle	BK, GY, LA, V, W	<input type="checkbox"/> TRUSBC20__

cULus Listed UL 498 and UL1310; NOM certified

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White).



Compliances, specifications and availability are subject to change without notice.



USB charging devices

Product description

2-pole, 3-wire grounding
 15A, 125V/AC, 5V DC 700MA; 15A, 125V/AC, 5V DC 2.4A
 15A, 125V/AC, 5V DC 3.1A
 20A, 125V/AC, 5V DC 3.1A

Design features

- Standard AC receptacle with two USB charging ports for conveniently charging most electronic components
- Dual USB charging ports charge most compatible electronic devices that charge via a 5V power adapter
- Three (3) pre-stripped 6" wire leads for line, neutral and ground for quick and easy installation (excluding TR7741)
- Tamper resistant receptacles provide compliance with 2014 NEC® Article 406.12 which states that all 15A and 20A, 125V/AC receptacles installed in dwelling units must be tamper resistant
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where jumper is used
- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Backwire clamps on side terminals provide for easy installation of #12 and #14 AWG wire (TR7741 only)
- Triple wipe blade contacts and double wipe ground contacts to ensure long-term plug retention
- Replaces a standard duplex receptacle and uses a decorator style wallplate



TR7741



TR7755



TR7756



TR8355

Combination USB charger with TR receptacle



Rating		USB Rating		Description	Color suffix	Catalog no.
A	V/AC	A	V/DC			
15	125	2.4	5	Combination USB charger with TR single receptacle	B, BK, GY, LA, V, W	□ TR7741__
15	125	3.1	5	USB charger with TR duplex receptacle, wire leads	B, BK, GY, LA, RB, SG, V, W	□ TR7755__
20	125	3.1	5	USB charger with TR duplex receptacle, wire leads	B, BK, GY, LA, RB, SG, V, W	□ TR7756__
15	125	3.1	5	USB charger with hospital grade TR duplex receptacle	GY, LA, RD, V, W	□ TR8255__
20	125	3.1	5	USB charger with hospital grade TR duplex receptacle	GY, LA, RD, V, W	□ TR8355__

cULus Listed UL 498 and UL1310; NOM certified

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: B (Brown), BK (Black), GY (Gray), LA (Light Almond), RB (Oil Rubbed Bronze), RD (Red), SG (Silver Granite), V (Ivory), W (White).

B	BK	GY	LA	RB	RD	SG	V	W
(Brown)	(Black)	(Gray)	(Lt. Almond)	(Oil Rubbed Bronze)	(Red)	(Silver Granite)	(Ivory)	(White)

Compliances, specifications and availability are subject to change without notice.



USB charging station



7750

Product description

5V/DC, 5.0A Total

Design features

- USB charging ports rated at 5.0 Amps total (2.5A top two ports, 2.5A bottom two ports)
- Three (3) pre-stripped 6" wire leads for line, neutral and ground for quick and easy installation
- Automatic grounding system eliminates need for bonding jumper in grounded metal enclosure and provides redundant measure of ground continuity where jumper is used
- Thermoplastic top and back-body are virtually unbreakable to deliver years of durable performance
- Steel mounting strap is zinc plated for added corrosion resistance
- Convenient patented built-in wire strippers speeds installation
- Replaces a standard duplex receptacle

USB charging station



USB Rating
A V/DC

Description

Color suffix

Catalog no.

5.0 5 USB multiport charging station

BK, GY, LA, V, W

□ 7750__

UL Listed to UL1310

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White).



We make what matters work.*

* At Eaton, we believe that power is a fundamental part of just about everything people do. Technology, transportation, energy and infrastructure-these are things the world relies on every day. That's why Eaton is dedicated to helping our customers find new ways to manage electrical, hydraulic and mechanical power more efficiently, safely and sustainably. To improve people's lives, the communities where we live and work, and the planet our future generations depend upon. Because that's what really matters. And we're here to make sure it works.

See more at Eaton.com/whatmatters

Visit our website:
www.eaton.com/wiringdevices

Electrical Sector
203 Cooper Circle
Peachtree City, GA 30269
United States
Eaton.com
Eaton.com/wiringdevices

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

© 2018 Eaton
All Rights Reserved
Printed in USA
Publication No. BR610030EN
June 2018

Electrical Sector
Canada Operations
5925 McLaughlin Road
Mississauga, Ontario, L5R 1B8
Canada
EatonCanada.ca
Eaton.com/wiringdevices

Eaton is a registered trademark.
All other trademarks are property
of their respective owners.

Electrical Sector
Mexico Operations -
Carr. Tlalnepantla -
Cuautitlan Km 17.8 s/n
Col. Villa Jardin esq.
Cerrada 8 de Mayo
Cuautitlan, Mexico CP 54800
Mexico
Eaton.mx
Eaton.com/wiringdevices

Follow us on social media to get the
latest product and support information.

